




VENDED LAUNDRY T-50X2 EXPRESS STACK DRYER



T-50X2 EXPRESS STACK DRYER

Dexter C-Series Dryer

Vended laundry solutions you can depend on.

Dexter C-Series vended dryers are engineered to show up for work in even the harshest laundry environments. Featuring upgraded controls and high quality materials, these fast and efficient dryers are designed to help make you more successful.

A store full of laundry equipment is a big investment and choosing the right equipment is an important decision. Our products will provide you the efficiency, flexibility, performance, and durability you need to be confident in your choice. With lifetime technical support and an industry leading 5-year limited warranty, you can be confident that we will stand behind every dryer you invest in.

Contact your Dexter Authorized Distributor today for more details.

EFFICIENT:

Perforated tumblers, balanced radial airflow, and the right amount of air recirculation provide maximum efficiency.

The anti-wrinkle feature offers an intermittent tumble to keep laundry wrinkle free.

DURABLE:

With heavy-duty bearings in cast iron bearing housings and a fully welded and painted cabinet, Dexter dryers are built to last.

Welded steel spider assemblies support the tumbler from the rear and eliminate the need for front support rollers.

The polished chrome or stainless steel doors and AISI 304 stainless steel panels keep dryers looking great year after year.

The screw resistant tumbler hole pattern minimizes tumbler damage.

RELIABLE:

Our industry leading 5-year warranty covers the trunnion, bearings, and bearing housing.

A 3-year parts warranty covers the rest.

We stand behind every machine you invest in with lifetime technical support.

PROFITABLE:

Every Dexter machine is now easier to use with a common user interface on all products, multiple language options, and detailed customer prompts.

C-Series controls work with DexterLive.com to allow you to create custom programs that fit your business.

A variety of PLUS cycle features and promotion options will help you maximize revenue generation.

INSTALLATION:

Stack dryers give you the power of two dryers in a single space.

With a single location for gas, electrical, and venting connections, Dexter stack dryers are easier to install and maintain.

OPTIONS:

Available with blue or black graphics, stainless steel or galvanized tumblers, chrome or stainless steel doors, and white or stainless steel panels.

Your dryers can be shipped with coin acceptors or payment system ready.

Gas models, with propane kits available.

This dryer is available as a reversing or non-reversing model.

Dexter C-Series stack dryers are available in 30lb and 50lb capacities.

EMPLOYEE OWNED | MADE IN THE USA | SINCE 1894

DEXTER.COM

2211 WEST GRIMES AVENUE, FAIRFIELD, IOWA 52556 USA

1.800.524.2954

T-50X2 EXPRESS STACK DRYER SPECIFICATIONS

Capacity:

Dry Weight Capacity - lb (kg)	2 x 50	(2 x 22.7)
Cylinder Volume (per tumbler) - cu ft (L)	15.8	(447.4)

Speed:

Tumbler Speed - RPM	45	---
Motor Size (per tumbler) - Standard - hp (kW)	0.75	(0.56)
Motor Size (per tumbler) - Reversing - hp (kW)	2 & 0.5	(1.5 & 0.38)

Airflow (per tumbler):

60 Hz Model - cfm (M3/min)	650	(18.4)
50 Hz Model - cfm (M3/min)	510	(14.4)

Dimensions:

Cabinet Height - in (cm)	79 1/4	(201.3)
Cabinet Width - in (cm)	34 1/2	(87.6)
Cabinet Depth - in (cm)	54 3/4	(139.1)
Door Opening - in (cm)	25 5/8	(65.1)
Floor to Lower Door Bottom - in (cm)	7	(17.8)
Floor to Upper Door Bottom - in (cm)	46	(116.8)
Cylinder Diameter - in (cm)	32 1/2	(82.6)
Cylinder Depth - in (cm)	33	(83.8)
Lint Screen Area (per tumbler) - sq in (sq cm)	544	(3510)

Weight:

Net Weight - lb (kg)	871	(395.1)
----------------------	-----	---------

Shipping Information:

Shipping Weight - lb (kg)	922	(418.2)
Shipping Height - in (cm)	84 1/4	(214)
Shipping Width - in (cm)	36	(91.4)
Shipping Depth - in (cm)	61 1/2	(156.2)

Gas Requirements (Gas Models Only):

Gas Supply Connection - in (mm)	1/2	(12.7)
Natural Gas Supply (Water Column) - in (cm)	5-8	(12.7 - 20.3)
LP Gas Supply (Water Column) - in (cm)	11 1/2 - 13 1/2	(29.2 - 34.3)

Gas Usage (Gas Models Only):

60Hz Model (per tumbler) - BTU/hr (kW)	108,000	(31.7)
50Hz Model (per tumbler) - BTU/hr (kW)	96,500	(28.3)


Electrical Requirements:

Gas Models (per stack dryer):

Model	Volts / Hz / Phase / Wiring	Circuit Breaker Amps / Running Amps / Wire Size / Rev
-11	208-240 / 60 / 1 / 2 wire + ground	20 / 15 / #12 / Reversing
-15	208-240 / 60 / 1 / 2 wire + ground	20 / 10 / #12 / Non-Reversing
-15	120 / 60 / 1 / 2 wire + ground	30 / 20 / #10 / Non-Reversing
-49	240 / 50 / 1 / 2 wire + ground	20 / 15 / 3.5 mm ² / Reversing
-49	240 / 50 / 1 / 2 wire + ground	20 / 10 / 3.5 mm ² / Non-Reversing
-59	230 / 50 / 1 / 2 wire + ground	20 / 10 / 3.5 mm ² / Non-Reversing

Installation Recommendations:

Minimum Clearance Between Machines - in (cm)	0	(0)
Minimum Clearance Behind Machines - in (cm)	18	(45.7)
Make-Up Air Required (per stack dryer) - sq ft (sq cm)	1.5	(1394)
Exhaust Size - in (cm)	8	(20.3)
Max. Exhaust Back Pressure (Water Column) - in (mm)	0.3	(7.6)
Recommended Exhaust Length - ft (m) & 2 elbows	14	(4.3)



Due to continuous product improvements specifications are subject to change, please consult Dexter Laundry, your Dexter Authorized Distributor or the installation manual for the most accurate information.

*Agency approvals vary based on machine configuration. Major approval bodies include ETL, CE and AGA.